

WHAT IS CLAIMED IS:

1. An apparatus for detecting a deterioration of an air-fuel ratio sensor, the deterioration detecting apparatus comprising:

5 air-fuel ratio sensor having an electrode on a solid electrolyte element for detecting an air-fuel ratio in an exhaust emission gas from an engine;

temperature adjusting means for adjusting a temperature of the solid electrolyte element in the air-fuel ratio sensor to at least two different predetermined temperatures; and

10 air-fuel ratio detection deterioration detecting means for detecting a deterioration of the air-fuel ratio sensor based on outputs of the air-fuel ratio sensor produced when the temperature of the solid electrolyte element is adjusted to the two different temperatures by the temperature adjusting means.

2. The apparatus for detecting a deterioration of an air-fuel ratio sensor according to Claim 1, wherein the temperature adjusting means adjusts the temperature and the air-fuel ratio detection deterioration detecting means detects the deterioration when the engine is in a predetermined same operating condition.

3. The apparatus for detecting a deterioration of an air-fuel ratio sensor according to Claim 1, wherein the air-fuel ratio detection deterioration detecting means detects the deterioration of the air-fuel ratio sensor by comparing the

outputs of the air-fuel ratio sensor relative to predetermined variations of the air-fuel ratio.

4. The apparatus for detecting a deterioration of an
5 air-fuel ratio sensor according to Claim 1, wherein the air-fuel
ratio detection deterioration detecting means detects the
deterioration of the air-fuel ratio sensor by comparing a response
of the air-fuel ratio sensor relative to predetermined variations
of the air-fuel ratio or a parameter related to an output
10 characteristic with respect to the exhaust emission gas.

5. The apparatus for detecting a deterioration of an
air-fuel ratio sensor according to Claim 4, wherein the response
or the parameter related to the output characteristic with respect
15 to the exhaust emission gas is at least one of an output variation
width, an output integrated value, an output differential value,
an integrated value of the output differential value, an output
period and an output frequency of the air-fuel ratio sensor.

20 6. The apparatus for detecting a deterioration of an
air-fuel ratio sensor according to Claim 1, wherein the
temperature adjusting means estimates the temperature of the solid
electrolyte element by detecting an internal resistance of the
air-fuel ratio sensor and adjusts the temperature of the solid
25 electrolyte element based on the estimated temperature.

7. The apparatus for detecting a deterioration of an

air-fuel ratio sensor according to Claim 6, wherein the temperature adjusting means determines an amount of heat for adjusting the temperature of the solid electrolyte element in accordance with an operating condition.

5

8. The apparatus for detecting a deterioration of an air-fuel ratio sensor according to Claim 1, wherein the temperature adjusting means supplies or stops the heat for adjusting the temperature of the solid electrolyte element under a predetermined operating condition.

10

9. The apparatus for detecting a deterioration of an air-fuel ratio sensor according to Claim 1, wherein the air-fuel ratio sensor is installed downstream from a catalyst.

15

10. The apparatus for detecting a deterioration of an air-fuel ratio sensor according to Claim 1, further comprising:
temperature adjusting failure detecting means for detecting a failure of the temperature adjusting means,

20

wherein the air-fuel ratio detection deterioration detecting means detects the deterioration of the air-fuel ratio sensor only when the failure is not detected by the temperature adjusting failure detecting means.